

Séria skrutkových kompresorov



OBS D (18-45 kW)

MODEL	Výkon motora		Vstupný tlak	Výstupný tlak	Kapacita (FAD)	Vstupný tlak	Výstupný tlak	Kapacita (FAD)	Vstupný tlak	Výstupný tlak	Kapacita (FAD)	Šírka (mm)	Dĺžka (mm)	Výška (mm)
	kW	HP	Bar	Bar	m3/min	Bar	Bar	m3/min	Bar	Bar	m3/min			
OBS 18 D	18.5	25	7	40	2.51	7	35	2.8	7	30	3.4	1400	2100	1555
			10		3.28	10		3.98	10		4.85			
			12		3.4	12		4.5	12		6.7			
OBS 22 D	22	30	7	40	2.96	7	35	3.58	7	30	4.4	1400	2100	1555
			10		4.24	10		5.02	10		6.19			
			12		4.68	12		5.68	12		7.09			
OBS 30 D	30	40	7	40	4.53	7	35	5.48	7	30	6.65	1400	2100	1555
			10		6.17	10		7.46	10		8.6			
			12		7.13	12		8.43	12		10.01			
OBS 37 D	37	50	7	40	5.7	7	35	6.8	7	30	7.8	1400	2100	1555
			10		7.82	10		9.15	10		10.61			
			12		10.06	12		10.55	12		12.44			
OBS 45 D	45	60	7	40	7.46	7	35	7.7	7	30	-	1400	2100	1555
			10		9.97	10		10.5	10		-			
			12		11.47	12		12.28	12		-			

- Výkon kompresora sa meria podľa normy ISO 1217: 2009 príloha C s ohľadom na vstupný tlak 1 bar a teplotu okolia 20 °C.