

Vysokotlakové sušičky vzduchu série ODR HP



ODR HP

MODEL	Prítok (m ³ /min)	Prítok (m ³ /h)	Napätie V / ~ / Hz	Veľkosť prípojky vstup - výstup	Odporúčané filtre	Max. Pracovný tlak (Bar)	Max. Okolité teplota °C	Max. Vstupná teplota °C
ODR 50 HP	0,83	50	230 V / 1 / 50 Hz	3/4"	OFL 100 HG-MX-MY-MA	50	55	60
ODR 90 HP	1,50	90	230 V / 1 / 50 Hz	3/4"	OFL 100 HG-MX-MY-MA	50	55	60
ODR 150 HP	2,50	150	230 V / 1 / 50 Hz	3/4"	OFL 300 HG-MX-MY-MA	50	55	60
ODR 220 HP	3,67	220	230 V / 1 / 50 Hz	3/4"	OFL 300 HG-MX-MY-MA	50	55	60
ODR 300 HP	5,00	300	230 V / 1 / 50 Hz	1 1/4"	OFL 300 HG-MX-MY-MA	50	55	60
ODR 400 HP	6,67	400	230 V / 1 / 50 Hz	1 1/4"	OFL 600 HG-MX-MY-MA	50	55	60
ODR 500 HP	8,33	500	230 V / 1 / 50 Hz	1 1/4"	OFL 600 HG-MX-MY-MA	50	55	60
ODR 575 HP	9,58	575	230 V / 1 / 50 Hz	1 1/4"	OFL 600 HG-MX-MY-MA	50	55	60
ODR 775 HP	12,92	775	230 V / 1 / 50 Hz	1 1/4"	OFL 850 HG-MX-MY-MA	50	55	60
ODR 910 HP	15,17	910	230 V / 1 / 50 Hz	1 1/4"	OFL 1200 HG-MX-MY-MA	50	55	60
ODR 1000 HP	16,67	1000	230 V / 1 / 50 Hz	2"	OFL 1200 HG-MX-MY-MA	50	55	60
ODR 1160 HP	19,33	1160	230 V / 1 / 50 Hz	2"	OFL 1200 HG-MX-MY-MA	50	55	60
ODR 1500 HP	25,00	1500	230 V / 1 / 50 Hz	2"	OFL 1600 HG-MX-MY-MA	50	55	60
ODR 1600 HP	26,67	1600	400 V / 3 / 50 Hz	2"	OFL 1600 HG-MX-MY-MA	50	55	60
ODR 1800 HP	30,00	1800	400 V / 3 / 50 Hz	2"	OFL 2500 HG-MX-MY-MA	50	55	60
ODR 2200 HP	36,67	2200	400 V / 3 / 50 Hz	2 1/2"	OFL 2500 HG-MX-MY-MA	50	55	60
ODR 2500 HP	41,67	2500	400 V / 3 / 50 Hz	2 1/2"	OFL 2500 HG-MX-MY-MA	50	55	60
ODR 2700 HP	45,00	2700	400 V / 3 / 50 Hz	2 1/2"	OFL 3000 HG-MX-MY-MA	50	55	60
ODR 3000 HP	50,00	3000	400 V / 3 / 50 Hz	2 1/2"	OFL 3000 HG-MX-MY-MA	50	55	60
ODR 3300 HP	55,00	3300	400 V / 3 / 50 Hz	2 1/2"	OFL 3000 HG-MX-MY-MA	50	55	60
ODR 3600 HP	60,00	3600	400 V / 3 / 50 Hz	2 1/2"	OFL 3000 HG-MX-MY-MA	50	55	60

- Kapacity sú špecifikované podľa normy ISO 1217: 2009, príloha C, s ohľadom na vstupný tlak 1 bar a teplotu okolia 20 °C. Rosný bod je +3 °C.

Tlak (Bar)	20	25	30	35	40	45	50	-	-	-	-
F1	1.19	1.1	1.07	1.04	1.02	1	0.98	-	-	-	-
Teplota okolia °C	-	-	-	-	20	25	30	35	40	42	-
F2	-	-	-	-	0.93	1	1.07	1.15	1.22	1.27	-
Vstupná teplota °C	-	-	-	-	30	35	40	45	50	55	60
F3	-	-	-	-	0.83	1	1.18	1.38	1.59	1.83	2.04

- Max. Tlak 50 Barg - Nominálny pracovný tlak 40 Barg