

Odlučovače vody s prírubou série OFL-WS



Séria prírub OFL-WS

| MODEL | Kapacita | | Veľkosť pripojenia |
|-----------|---------------------|-------------------|--------------------|
| | m ³ /min | m ³ /h | |
| F 2500WS | 41.67 | 2500 | DN80 |
| F 3200WS | 53.33 | 3200 | DN100 |
| F 4300WS | 71.67 | 4300 | DN100 |
| F 6500WS | 108.33 | 6500 | DN150 |
| F 8500WS | 141.67 | 8500 | DN150 |
| F 11000WS | 183.33 | 11000 | DN200 |
| F 14000WS | 233.33 | 14000 | DN200 |
| F 17000WS | 283.33 | 17000 | DN250 |
| F 21000WS | 350.00 | 21000 | DN250 |
| F 25500WS | 425.00 | 25500 | DN300 |
| F 30000WS | 500.00 | 30000 | DN300 |

- Max. Odporúčaná pracovná teplota: 80 °C

- Min. Odporúčaná pracovný tlak: 1,5 °C

- Hodnota poklesu tlaku: 50 mbar

| Korekčné faktory | | | | | | | | |
|----------------------|------|------|------|------|------|------|------|------|
| Pracovný tlak (barg) | 1 | 3 | 5 | 7 | 9 | 11 | 13 | 14 |
| PSIG | 15 | 44 | 73 | 100 | 130 | 160 | 189 | 200 |
| X1 | 0,50 | 0,71 | 0,87 | 1,00 | 1,12 | 1,22 | 1,32 | 1,38 |